



CityStar

BRP334 LED144 CW R5C FG PSU S1

CityStar is a state-of-the-art LED luminaire at a surprisingly affordable price. Building on the strengths of best choice of LEDs and Electronics, this set of luminaire is designed to provide a cost-effective solution to those looking to reduce energy costs. CityStar offers all the advantages of LED lighting, without the high cost associated with this technology. The CityStar range is the perfect solution for replacing luminaires fitted with high-pressure sodium, metal halide and other HID lamps. Concept CityStar is composed of a high-pressure, die-cast aluminium body, universal fixation and a polycarbonate protector with integrated lenses. For optimized heat dissipation, the electronic components and the LED engine are in separate compartments. The body integrates cooling fins to maintain performance in the long term. Available in five different sizes CityStar is a very efficient LED lighting solution for streets, roads and any other outdoor environments where it is crucial to maximize energy savings.

Warnings and Safety

- Class I Protection

Product data

General Information		Operating and Electrical	
Driver included	Yes	Beam angle of light source	120 degree(s)
Light source engine type	LED	Light source color	757 cool white
Warranty period	3 years	Optical cover type	Polycarbonate
Flammability mark	For mounting on normally flammable surfaces	Luminaire light beam spread	130° x 88°
Light Technical		Optic type outdoor	Distribution Symmetric Wide
Luminous Flux	14,400 lumen	Input Voltage	140-270 V
Correlated Color Temperature (Nom)	5700 K	Line Frequency	50 Hz
Luminous Efficacy (rated) (Nom)	120 lm/W	Power Consumption	120 W
Color rendering index (CRI)	>70		

Power Factor (Fraction)	0.95
Temperature	
Ambient temperature range	-10 to +50 °C
Controls and Dimming	
Dimmable	No
Control interface	-
Mechanical and Housing	
Housing Material	Aluminium pressure die cast
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Housing Color	Aluminum and gray
Mounting device	Spigot for diameter 34 to 76 mm
Material	Aluminum
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]

Mech. impact protection code	IK07 [2 J reinforced]
Surge Protection (Common/Differential)	4/4 kV
Protection class IEC	Safety class I
Initial Performance (IEC Compliant)	
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Median useful life L70B50	50,000 hour(s)
Product Data	
Order product name	BRP334 LED144 CW R5C FG PSU S1
Order code	919515815625
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	2
Material Nr. (12NC)	919515815625
Full product name	BRP334 LED144 CW R5C FG PSU S1

Dimensional drawing

