

# OPTICAL FIBRE LAUNCH CABLES

A MUST-HAVE FOR OTDR USERS

**150 m  
SNGLE MODE FIBER**

**150 m  
MULTI MODE FIBER**

**1000 m  
SINGLE MODE FIBER**



**SINGLE MODE  
& MULTI MODE**

*Available in the most suitable fiber formats.*



**LOW  
ATTENUATION**

*Attenuation losses are as low as 0.9 dB/km max.*



**EASY TO  
HANDLE**

*Practical, compact design.*



**LONG  
LIFETIME**

*More than 1000 mating cycles.*



**MAGNETIZED  
FRAME**

*It sticks to metal parts such as racks.*

| LAUNCH CABLES      | AF-016               | AF-017                 | AF-018               |
|--------------------|----------------------|------------------------|----------------------|
| FIBER TYPE         | Singlemode           | Multimode              | Singlemode           |
| LENGTH             | 150 m                | 150 m                  | 1000 m               |
| CONNECTORS         | SC/SC                | SC/SC                  | SC/SC                |
| WAVELENGTH         | From 1310 to 1650 nm | From 850 nm to 1300 nm | From 1310 to 1650 nm |
| ATTENUATION        | -0.3 dB/km max.      | -0.9 dB/km max.        | -0.3 dB/km max.      |
| CONNECTOR LIFETIME | > 1000 mating cycles | > 1000 mating cycles   | > 1000 mating cycles |

