



PE-005

AUDIO IMPEDANCE TESTER

WITH TRIPLE TEST RANGE

MEASUREMENT OF IMPEDANCES AT 1 kHz

IT ALLOWS TESTING OF HOME THEATER, AUDITORIUMS AND SPEAKER SYSTEMS

TEST RANGES AT 20 Ω, 200 Ω AND 2000 Ω

DATA HOLD FUNCTION

TIMER FUNCTION FOR HANDS-FREE CONTINUOUS OPERATION



The audio impedance tester **PE-005** allows testing of home theater and speaker system for estimate the necessary power in an installation for the suitable election of the amplifier.

There are three user-selectable measurement ranges (20, 200 and 2000 Ω) and a 1 kHz test frequency.

The timer function allows free hands continuous operation of the **PE-005** audio impedance tester: It is activated automatically after 3 to 5 minutes since the user presses the TEST ON/OFF button stopping the measurement until a new TEST ON/OFF pulsation

SPECIFICATIONS	PE-005
Measurement ranges	20 Ω / 200 Ω / 2000 Ω
Test frequency	1 kHz
Accuracy	
20 Ω scale	±2% rdg ± 2 digits or ±0.1 Ω, which is greater.
200 / 2000 Ω scales	±2% rdg ± 2 digits
Display	LCD screen 3 ½ digits (2000 counts)
Power supply	9 V DC (6 batteries x 1.5 V type R6)
Mechanical features	
Dimensions	90 (W.) x 205 (H.) x 55 (D.) mm
Weight	550 g approx. (including batteries)
Included accessories	PP010 Test leads with safety clamps User manual Transport suitcase

